

ID-2.5 inch SATA SSD 3SE-P



- 2.5" SATA III solution for industrial field
- Build-in DRAM buffer
- iSMART disk health monitoring
- Intelligent error recovery system
- Excellent data transfer speed
- Enhanced power cycling management

Specifications

Interface	SATA III
Flash Type	SLC
Flash P/E Cycle Limit	100,000
Capacity	8GB~256GB
Max. Channels	4
Sequential R/W (MB/sec, max.)	510 / 340
Max. Power Consumption	3.0W (5V x 600 mA)
Thermal Sensor	WT Only
External DRAM Buffer	√
H/W Write Protect	-
Pin7 Power	-
ATA Security	√
S.M.A.R.T.	√
Dimension (WxLxH)	69.85 X99.85 X 9.20 mm
Environment	Vibration: 20G @7~2000Hz Shock: 1500G @ 0.5ms Storage Temperature: -55°C ~ +95°C MTBF: 3 million hours

Ordering Information

Operation Temp.	8GB	16GB	32GB	64GB	128GB	256GB
Standard Grade (0°C ~ +70°C)	DES25-08GD67SCAQB	DES25-16GD67SCAQB	DES25-32GD67SCAQB	DES25-64GD67SCAQB	DES25-A28D67SCAQB	DES25-B56D67SCAQB
Industrial Grade (-40°C ~ +85°C)	DES25-08GD67SWAQB	DES25-16GD67SWAQB	DES25-32GD67SWAQB	DES25-64GD67SWAQB	DES25-A28D67SWAQB	DES25-B56D67SWAQB