


# SATA Slim

## 3SE3 series

### Drawing



## Specifications

Interface	SATA III
Flash Type	SLC
Capacity	8GB~128GB
Max. Channels	4
Sequential R/W (MB/sec, max.)	370 / 220
Max. Power Consumption	2W (5V x 400 mA )
Thermal Sensor	ST- Optional/WT- Default
External DRAM Buffer	-
H/W Write Protect	-
Pin7 Power	-
ATA Security	√
S.M.A.R.T.	√
Dimension (WxLxH)	54.0 X 39.0 X 4.0 mm
Environment	Vibration: 20G @7~2000Hz Shock: 1500G @ 0.5ms Storage Temperature: -55°C ~ +95°C MTBF: 3 million hours

## Ordering Information

Operation Temp.	8GB	16GB	32GB	64GB	128GB
Standard Grade (0°C ~ +70°C)	DESLM-08GD08SCAQB	DESLM-16GD08SCAQB	DESLM-32GD08SCAQB	DESLM-64GD08SCAQB	DESLM-A28D08SCAQB
Industrial Grade (-40°C ~ +85°C)	DESLM-08GD08SWAQB	DESLM-16GD08SWAQB	DGSLM-32GD08SWAQB	DESLM-64GD08SWAQB	DESLM-A28D08SWAQB