

IDK-2115

15" XGA 1,200 cd/m² Ultra High Brightness Industrial Display Kit with LED B/L

NEW



Features

- 15" LCD supports 1024 x 768 pixels and wide operating temperature (-20 ~ 70° C)
- Ultra-high brightness of 1200 cd/m² with LED backlight
- High contrast ratio of 700:1
- High uniformity of 85%
- Superior sunlight readability
- LVDS signal interface
- Low power consumption 16.06 W
- 5W resistive touch solution (optional)
- Anti-Reflection surface treatment (optional)
- Manually VR brightness control (optional)
- Auto-dimming solution with light sensor (optional)
- Optical bonding (optional)

Introduction

The Advantech IDK-2115 series comes with a 15" 1200 cd/m² industrial grade LCD display, and an LED driver board. The series is also available with flexible options for 5-wire touch screens and enhanced treatment such as anti-reflection surface treatment and optical bonding solution. IDK-2115 series supports 1200 cd/m² high brightness with low power consumption at the maximum consumption of 16.06 W. Equipped with high level of brightness and wide operating temperature, IDK-2115 provides superior sunlight readability and is perfect for applications whether in semi-outdoor or outdoor environments.

Specifications

LCD Panel	Model	IDK-2115	IDK-2115 (Wide temp)
	Size	15" LED backlight panel	15" LED backlight panel
	Resolution	1024 x 768 (XGA)	1024 x 768 (XGA)
	Viewing Angle (U/D/L/R)	80°/80°/85°/85°	70°/70°/80°/80°
	Brightness	1200 (cd/m ²)	1200 (cd/m ²)
	Contrast Ratio	700 : 1	700 : 1
	Response Time (ms)	8 ms	25 ms
	Colors	6bit (262K)/8bit (16.2M)	6bit (262K)/8bit (16.2M)
	Voltage	3.3 V	3.3 V
	Consumption	16.06 W	16.06 W
	Signal Interface	1 channel LVDS	1 channel LVDS
Weight	N series: 1350 g	N series: 1350 g	
	R series: 1600 g	R series: 1600 g	
Dimensions (W x H x D)	N series: 326.5 x 253.5 x 12.0 mm	N series: 326.5 x 253.5 x 11.5 mm	
	R series: 326.5 x 253.5 x 14.6 mm	R series: 326.5 x 253.5 x 14.4 mm	
LED Driver Board	Efficiency	85%	85%
	Output Current & Voltage	800 mA / 17.7 V (Min)	800 mA / 18.1 V (Min)
	Dimensions (W x H x D)	80 x 50 x 7 mm	80 x 50 x 7 mm
Touch Screen (R series)	Touch Screen	5-wire Resistive	5-wire Resistive
	Transparency	80± 3%	80± 3%
	Durability	10 million times	10 million times
Environment	Operating Temperature	0 ~ 65° C	-20 ~ 70° C
	Storage Temperature	-20 ~ 65° C	-40 ~ 80° C
	Humidity	8 ~ 90% @ 39°C., non-condensing	8 ~ 90% @ 39°C., non-condensing

