

DH110

Drive 4K and Rich Interactive Content with Intel® skylake platform



Focused on 4K vertical markets, Shuttle launches a new generation slim PC DH110, equipped with Intel® H110 chipsets support the latest Intel® 6th generation Skylake LGA1151 65W processors. With Intel® built-in HD graphics engine, DH110 can support 4K/Ultra HD video playback. With a body thickness of only 43mm and VESA mountable design, the DH110 make it easy to fit

commercial applications with limited space.

FORM FACTOR	1.3L chassis	
PROCESSOR	Support Intel Skylake Core i3/i5/i7, Pentium, Celeron CPU max. TDP 65W	
CHIPSET	Intel H110 Express chipset	
MEMORY	2 x 204 pin DDR3L SODIMM slots,16GB per DIMM (Max 32GB) Dual Channel DDR3L 1600 Mhz	
VGA	HDMI x1 + DisplayPort x1 Support dual display 4K playback (Dual channel memory recommended)	
AUDIO	Realtek ALC662 channel High Definition Audio	
ETHERNET	Intel i211+i219LM Dual Lan 100Mb/s and 1Gb/s operation	Support Wake-On-LAN function Support Teaming function
STORAGE INTERFACE	SATA 6.0Gb/s interface	
ONBOARD CONNECTORS	(1) SATA 6 connectors (1) SATA power connector (1) 4pin fan connector (1) Front audio header	(1) 1x4 pin USB header (1) D-sub connector (1) Auto power on header (1) External Power on (1) RS232 voltage switch
FRONT PANEL	(1) Power-On button (1) Power LED (1) HDD LED (2) USB 2.0 port	(2) USB 3.0 port (1) Earphone-Out (1) Microphone-In (1) SD Card reader
BACK PANEL	(1) External power on/Clear CMOS header (2) USB 3.0 port (1) HDMI port (1) DisplayPort (1) eSATA+USB2.0 COM port (2) RJ45 Gigabit LAN port	(1) RS232 (1) RS232/RS422/RS485 (1) PS/2 port (1) DC in (1) Kensington lock (2) Wireless Antenna fixture
DRIVE BAYS	(1) 2.5" HDD / SSD bay	
DIMENSIONS	190(L) x 165(W) x 43(H) mm	
POWER	90W Power Adapter Input:100- 240V AC Output: 19V 4.47A DC	
ACCESSORIES	XPC Multilanguage Quick User Guide XPC DVD Driver VESA mount VESA mount quick installation guide	1* Power cord 1* SATA cable Screws Optional 802.11b/g/n WLAN module
EXPANSION SLOT	(1) M.2 2260 Type M key socket (1) M.2 2230 Type A,E Key socket	
OS SUPPORT	Windows 7 Windows 8.1	Windows 10 Linux