## W22IT3S-SPA3

## 21.5" Intel® Core™ i5-1135G7 IP65 Stainless PCAP Chassis Panel PC



## **KEY FEATURES**

- 11th Generation Intel® Core™ i5-1135G7 2.4GHz (up to 4.2GHz)
- SUS 316/ AISI 316 stainless steel for food and chemical industries
- Sealed to IP65 for protection against water and dust
- A true flat, easy-to-clean front surface with edge-to-edge design
- Flat multi-touch panel pc with superior readability and P-Cap technology
- Various mounting solutions, Yoke mount and VESA mount
- Plenty of I/O s including USB 2.0, RS232 serial port and RJ45-10/100/1000 LAN ports
- Waterproof ports with adapter cables for external connectivity
- Support Glove / Rain mode
- Optical bonding (optional)



## **SPECIFICATIONS**

Display				
Resolution	1920x1080	Size	21.5 inches	
Contrast Ratio	3000:1	Panel Brightness	250.0 nits	
View Angles	89,89,89,89	Active Area	476.64x268.11 mm	
Touch / Glass	Projected Capacitive Multi Touch Screen			
System Specification				
WLAN	Support (Optional)	ВТ	Support (Optional)	
Processor	Intel Core i5-1135G7 2.4GHz (up to 4.2GHz)	Memory	1 x SO-DIMM, DDR4 3200 MHz, 4GB 8GB (Optional) 16GB (Optional) 32GB (Optional)	
Storage	1 x M.2 M-Key 2242 SATA SSD or 1 x M.2 M-Key 2280 NVMe SSD 128GB 256GB (Optional) 512GB (Optional) 1TB(for NVMe) (Optional) 2TB(for NVMe) (Optional) 4TB(for NVMe) (Optional) 1 x SATA III , up to 2TB (Optional)	Ethernet controller	2 x Intel® Ethernet Controller	
Security	TPM 2.0	Operating System	Windows 11 IoT Enterprise SAC (64 bit) (Optional) Windows 11 Pro 64 bit (Optional) Windows 10 IoT Enterprise (64 bit) (Optional) Linux Ubuntu 22.04 (Optional)	
Mechanical				
Dimension	541 x 337 x 56.2 mm	Mounting	VESA Mount Yoke Mount	
Enclosure	Stainless Housing	Cooling System	Fanless design	
Environment				
Operating Humidity	10% to 90% RH, Non-Condensing	Operating Temperature	0°C to 45°C	
Storage Temperature	-20°C to 60°C	IP rating	IP65	

Certification			
Certification	CE, FCC		
IO Ports			
Power Input	1 x M12 waterproof connector for 12V DC	USB Port	1x M12 waterproof connector for 2 x USB2.0
Serial Port	1 x M12 waterproof connector for RS232	LAN	1 x waterproof Giga LAN RJ45 connector
Indicator	1 x LED Indicator for power 1 x LED Indicator for storage		
Control			
Button	1 x Power Button 1 x Reset Button		
Accessory			
Accessory	100~240V AC to DC Adapter with waterproof connector Power Cord External USB cable with waterproof connector External COM cable with waterproof connector External LAN cable with waterproof connector Waterproof caps VESA screws		
Power			

**DIMENSIONS** UNIT:MM

12V DC (M12 type)

**Power Rating** 

USB Type-A
LAN
SCOM
WFI Antenna Cover (Optional)