## W24IAD3S-SPA2-R

## 23.8" Intel® Core™ i5-1235U IP65 Stainless R Series Panel PC



1 x M12 waterproof connector for RS232

## **KEY FEATURES**

- 12th Generation Intel® Core™ i5-1235U 3.3GHz(up to 4.40 GHz)
- Round corner design
- A true flat, easy-to-clean front surface with an edge-to-edge design
- Sealed to IP65 for protection against water and dust
- Support Glove / Rain mode
- SUS 316 / AISI 316 stainless steel for food and chemical industries

1 x waterproof Giga LAN RJ45 connector

- Various mounting solutions
- Optical bonding (optional)



## **SPECIFICATIONS**

**Serial Port** 

Display			
Resolution	1920x1080	Size	23.8 inches
Contrast Ratio	3000:1	Panel Brightness	250.0 nits
View Angles	89,89,89,89	Active Area	527.04x296.46 mm
Touch / Glass	Projected Capacitive Multi Touch Screen		
System Specification			
WLAN	Support (Optional)	ВТ	Support (Optional)
Processor	Intel® Core™ i5-1235U 3.3GHz(up to 4.40 GHz)	Memory	1 x SO-DIMM, DDR5 4800 MHz, 8GB 16GB (Optional) 32GB (Optional)
Storage	1 x M.2 2280 M-Key NVMe SSD 256GB 512GB (Optional) 1TB (Optional) 2TB (Optional) 1 x SATA III for 2.5" SSD/HDD up to 2TB (Optional)	Ethernet controller	2 x Intel® Ethernet Controller
Security	TPM 2.0	Operating System	Windows 11 IoT Enterprise (64 bit) (Optional) Windows 11 Pro 64 bit (Optional) Linux Ubuntu 22.04(Do not support Wake on Touch) (Optional)
Mechanical			
Dimension	620 x 390 x 56 mm (with junction box) 620 x 390 x 153 mm (without junction box)	Mounting	VESA mount Yoke mount (Optional) Arm mount (Optional)
Enclosure	Stainless Housing	Cooling System	Fanless Design
Environment			
Operating Humidity	10% to 90% RH, Non-Condensing	Operating Temperature	0°C to 45°C
Storage Temperature	-20°C to 60°C	IP rating	IP65
Certification			
Certification	CE, FCC		
IO Ports			
Power Input	1 x M12 waterproof connector for 12V DC	USB Port	1x M12 waterproof connector for 2 x USB2.0

LAN

Control 1 x Power Button **Button** 1 x Reset Button Accessory Accessory 100~240V AC to DC Adapter with waterproof connector Power Cord External USB cable with waterproof connector External COM cable with waterproof connector External LAN cable with waterproof connector Junction Box Waterproof caps Manual VESA screws Power **Power Rating** 12V DC (M12 type) **DIMENSIONS** UNIT:MM

Indicator

1 x LED Indicator for power 1 x LED Indicator for storage

