




1099L 10-inch LCD

Outdoor Open-Frame
Touchscreen Display



**Optically Bonded
1000 NIT Display**



**Direct Sunlight
Readability**



**Built-in
Temp Control**

Product Overview

Elo's 1099L 10-inch outdoor open-frame touchscreen monitor has you covered 24/7 with wide viewing angle technology and 1000 NITs of brightness. The IK09, vandal-proof outdoor display offers direct sunlight readability viewable with polarized sunglasses and extended operating temperatures. From payment and ticketing machines to signage and charging stations, the brilliant, optically bonded weatherproof monitor offers locking connectors and supports 12v-24v DC for easy and secure integration into an enclosure.

The 1099L provides outstanding image clarity and light transmissivity, as well as stable, drift-free operation for accurate touch responses making it well-suited for almost any commercial kiosk application.

Optimize outdoor performance with the ambient light sensor that automatically adjusts the display's brightness to save power and extend the life of the panel.

Mount in landscape, portrait and upward facing orientations, providing optimal flexibility for integrating in any counter, kiosk or cabinet design.

Built for integration into harsh physical and thermal environments: IK09 impact protection with -20C to 60C operating temperatures.

1099L 10-inch Open-Frame Touchscreen Display

| Specifications | |
|-----------------------------|---|
| Model | 1099L |
| Color | Black |
| Active Display Area | 8.54" x 5.33" / 216.96 mm x 135.60 mm |
| Diagonal | 10.1" |
| Aspect Ratio | 16:10 |
| Native Resolution | 1280x800 |
| Other Supported Resolutions | 640x480 60Hz; 720x400 70Hz; 800x600 60Hz; 1024x768 60Hz; 1280x800 60Hz |
| Number of Colors | 16.7 million |
| Number of Touches | 5-touch with USB, 2-touch with touch-thru |
| Brightness (typical) | With TouchPro PCAP: 1000 nits |
| Response (typical) | 25 msec |
| Viewing Angle | Horizontal: 85°/170°; Vertical: 85°/170° |
| Contrast Ratio | 800:1 |
| On-Screen Display | Accessible through switches on the unit's tethered OSD Control box. Controls: Menu, Up, Down, Select, Power Brightness, Contrast, Light sensor, Clock, Phase, H-Position, V-Position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Rotation, OSD Language, OSD H-Position, OSD V-Position, Recall Defaults, Video Priority, Information, Touch on Sleep Mode, Touch Through, Touch Interface, GPIO Control, Time Setting, On/Off Schedule, Daylight Saving Time Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese Lockouts: OSD, Power |
| I/O Ports | Locking for all ports, including USB TypeB, RJ45 for OSD remote key, VGA, HDMI, DisplayPort |
| Video | HDMI V1.3 Type A receptacle for HDMI input Analog VGA on Female DE-15 (DB-15) connector DisplayPort V1.1a - Supports later versions of DisplayPort video input Input Video Horizontal Sync frequency range: 31.5 - 80 KHz Input Video Vertical Sync (frame rate) frequency range: 60-75Hz |
| Power | External DC - Optional power brick (sold separately) Monitor input power connector: Coaxial power jack (2.5mm (+0.0 -0.1mm) pin outer diameter, 5.7mm (+/- 0.1mm) barrel inner diameter, 7.8mm (+/- 0.2mm) barrel depth) Monitor input voltage range: 12V - 24V DC +/- 5% Adapter output power connector: DC barrel plug (2.5mm (+/- 0.1mm) pin inner diameter, 5.5mm (+/- 0.05mm) barrel outer diameter, 7.5mm (+/- 0.5mm) barrel length) Adapter input voltage range: 100-240 VAC Input frequency: 50-60 Hz |
| Power Consumption | Monitor + adapter - ON: 23 W; SLEEP from PC: 1.5 W ; OFF: 1.5 W |
| Temperature | Operating: -20 °C to 60 °C (-4 °F to 140 °F); Storage: -30 °C to 80 °C (-22 °F to 176 °F) |
| Humidity | Operating: 10% to 90%; Storage: 10% to 95% (38.7° maximum wet bulb temperature) |
| Dimensions | 10.08" x 6.93" x 1.61" / 256 mm x 176 mm x 41 mm |
| Shipping Dimensions | 13.58" x 10.94" x 6.89" / 345 mm x 278 mm x 175 mm |
| Weight | Unpackaged: 1.67 kg / 3.68 lbs, Packaged: 3.6 kg / 7.94 lbs |
| Mounting Options | 75mm VESA mount on rear of unit; 2 hole mounting interface on all four sides; Flush mount with included brackets |
| Warranty | 2 years standard |
| MTBF | 50,000 hours demonstrated |
| Agency Approvals | Australia RCM; Canada cUL, IC; China CCC; Europe CE, TUV; United Kingdom UKCA; Japan VCCI; Korea KCC; Mexico NoM; Taiwan BSMI; United States UL, FCC; International CB; RoHS, China RoHS, WEEE |
| Compliance | GLI 27 kV air / 8 kV contact ESD compliance; UL ball-drop compliance; IK09 impact compliance |
| Other Features | Viewable with polarized sunglasses in portrait and landscape orientations. Ambient light sensor. Thermal sensor. External fans (Automatically controlled) |
| What's in the Box | 1099L, HDMI Cable (screw-locking type), VGA Cable, OSD Remote, Touch USB Cable (screw-locking type), QIG, Flush Mount Brackets with screws, EEI Label, Japan Class-B TM info sheet |

Ordering Information

| Part Number | Technology | Interface | Surface Treatment |
|-------------|---------------|-----------|-------------------|
| E354792 | TouchPro PCAP | USB2.0 | Anti-Glare |

Learn more about Elo at [EloTouch.com](https://www.elotouch.com).

Americas

Tel +1 408 597 8000
elosales.na@elotouch.com

Europe (EMEA)

Tel +32 16 930 136
EMEA.Sales@elotouch.com

Asia Pacific

Tel +86 (21) 3329 1385
EloAsia@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, the Elo Backpack, EloView and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2024 Elo Touch Solutions, Inc. All rights reserved. 24021AES00185

