

IoT SuperServer SYS-212B-FN2T

X14 2U compact front I/O edge AI system with up to 5 PCIe 5.0 slots and redundant AC/DC PSU

Key Applications



5G Core and Edge, AI Inference and Machine Learning, Network Function
Virtualization, Healthcare, Retail,

Key Features

- Single Intel® Xeon® 6 6700 series processors with E-cores;
- 8 DIMM slots supporting up to 1TB of memory;
- Optional PCIe slot configurations up to 4 PCIe 5.0 x16 (3 FHFL+1 HHHL) slots with support for double-width GPU/Accelerator cards;
- 2x M.2 M-Key NVMe 2280/22110;
- 2x RJ45 10GbE LAN and 1xRJ45 1GbE dedicated IPMI LAN;
- Optional 4 x 2.5" hot-swap NVMe drive bays;



Form Factor	2U Rackmount Enclosure: 437 x 89 x 450mm (17.2" x 3.5" x 17.72") Package: 590 x 370 x 665mm (23.23" x 14.57" x 26.18")
Processor	Single Socket E2 (LGA-4710) Intel® Xeon® 6700 series processors with E-cores Up to 144C/144T; Up to 108MB Cache
GPU	Max GPU Count: Up to 3 single-width GPUs CPU-GPU Interconnect: PCIe 5.0 x16 CPU-to-GPU Interconnect GPU-GPU Interconnect: PCIe
System Memory	Slot Count: 8 DIMM slots Max Memory (1DPC): Up to 1TB 6400MT/s ECC DDR5 RDIMM
Drive Bays Configuration	Default: Total 4 bays <ul style="list-style-type: none"> • 4 rear hot-swap 2.5" NVMe* drive bays (*NVMe support may require additional storage controller and/or cables) M.2: 2 M.2 NVMe slots (M-key 2280/22110)
Expansion Slots	PCI-Express (PCIe) Configuration: Default <ul style="list-style-type: none"> • 2 PCIe 5.0 x16 (in x16) FHFL slots Option A* <ul style="list-style-type: none"> • 2 PCIe 5.0 x16 (in x16) FHFL slots • 1 PCIe 5.0 x16 (in x16) FHFL double-width slot • 1 PCIe 5.0 x16 (in x16) HHHL slot • 1 PCIe 5.0 x8 (in x8) HHHL slot Option B* <ul style="list-style-type: none"> • 2 PCIe 5.0 x16 (in x16) FHFL slots • 1 PCIe 5.0 x16 (in x16) HHHL slot M.2: 2 M.2 NVMe slots (M-key)
On-Board Devices	NVMe: NVMe; RAID 0/1 support(Intel® VROC RAID key required) Chipset: System on Chip Network Connectivity: 2 RJ45 10GBASE-T with Intel® X710-AT2
Input / Output	LAN: 1 RJ45 1 GbE Dedicated BMC LAN port 2 RJ45 10 GbE LAN ports USB: 2 USB 3.2 Gen1 Type-A ports(front) Video: 1 VGA port



*Requires additional parts from the optional parts list, and limits processor to lower TDP

System Cooling	Fans: 4x 4-PIN PWM 8cm Fan(s)
Power Supply	1x 2000W Redundant Titanium Level (96%) power supply
System BIOS	BIOS Type: AMI 256MB SPI Flash
Management	SuperCloud Composer; Supermicro Server Manager (SSM); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!
PC Health Monitoring	CPU: Monitors for CPU Cores, Chipset Voltages, Memory FAN: Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment CPU thermal trip support, PEPI
Dimensions and Weight	Weight: Gross Weight: 29 lbs (13.18 kg) Net Weight: 21 lbs (9.55 kg) Available Color: Black
Operating Environment	Operating Temperature: 0°C ~ 40°C (32°F ~ 104°F) Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)
Motherboard	Super X14SBM-TF
Chassis	CSE-223M-R000RCNDP