

# BigTwin SuperServer SYS-622BT-DNC8R

2U 2-Node BigTwin with 6 hot-swap 3.5" NVMe/SAS/SATA drives per node



## Key Applications

Hyperconverged Infrastructure, Scale-Out Object Storage, Back-up & Recovery,


## Key Features

- Dual Socket E2 Intel® Xeon® 6 6700 series processors with E-cores up to 250W with air cooling or 330W with liquid cooling;
- Up to 16 DIMMs supporting up to 4TB DDR5-6400 in 1DPC;
- Flexible networking with OCP 3.0 AIOM slot;
- Up to 2 PCIe 5.0 x8 LP + 1 PCIe 5.0 x16 LP slots  
Internal PCIe 5.0 for 2x NVMe M.2 support onboard  
Optional 4x NVMe M.2 support onboard with built-in HW RAID1 via SCC-A2NM2241GH-B1;
- Up to 6 front hot-swap 3.5" NVMe/SAS drive bays;
- Two **hot-pluggable** systems (nodes) in a 2U form factor. Each node supports the following;;




Form Factor	2U Rackmount Enclosure: 449 x 88 x 774mm (17.68" x 3.47" x 30.5") Package: 626 x 248 x 1150mm (24.65" x 9.76" x 45.28")
Processor	Dual Socket E2 (LGA-4710) Intel® Xeon® 6700 series processors with E-cores Up to 144C/144T; Up to 108MB Cache per CPU
System Memory	Slot Count: 16 DIMM slots Max Memory (1DPC): Up to 4TB 6400MT/s ECC DDR5 RDIMM
Drive Bays Configuration	Default: Total 6 bays <ul style="list-style-type: none"> <li>• 2 front hot-swap 3.5" PCIe 5.0 NVMe/SAS drive bays</li> <li>• 4 front hot-swap 3.5" PCIe 4.0 NVMe/SAS drive bays</li> </ul> M.2: 2 M.2 PCIe 5.0 x4 NVMe slots (M-key 22110(default); VROC required for RAID)
Expansion Slots	Default <ul style="list-style-type: none"> <li>• 2 PCIe 5.0 x8 LP slots</li> <li>• 1 PCIe 5.0 x16 LP slot</li> <li>• 1 PCIe 5.0 x16 AIOM slot (OCP 3.0 compatible)</li> </ul>
On-Board Devices	SAS: SAS (12Gbps) via Broadcom® 3808; (IT mode) Chipset: System on Chip Network Connectivity: Via AIOM
Input / Output	LAN: 1 RJ45 1 GbE Dedicated BMC LAN port USB: 2 USB 3.0 Gen2 Type-A ports(Rear) Video: 1 VGA port

(Front View – System)



(Rear View – System)



System Cooling	<p>Fans: 4x 14.9K RPM Heavy Duty 80x80x38mm Fan(s)</p> <p>Liquid Cooling: Direct to Chip (D2C) Cold Plate (optional)</p>
Power Supply	2x 2200W Redundant (1 + 1) Titanium Level (96%) power supplies
System BIOS	BIOS Type: AMI 32MB Flash ROM
Management	SuperCloud Composer; Supermicro Server Manager (SSM); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!
PC Health Monitoring	<p>FAN: Fans with tachometer monitoring</p> <p>Status monitor for speed control</p> <p>Pulse Width Modulated (PWM) fan connectors</p> <p>Temperature: Monitoring for CPU and chassis environment</p> <p>CPU: Monitors for CPU Cores, Chipset Voltages, Memory.</p> <p>8+4 Phase-switching voltage regulator</p>
Dimensions and Weight	<p>Weight: Gross Weight: 80.7 lbs (36.6 kg)</p> <p>Net Weight: 55.1 lbs (25 kg)</p> <p>Available Color: Black front &amp; silver body</p>
Operating Environment	<p>RoHS Compliant</p> <p>Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F)</p> <p>Non-operating Temperature: -30°C to 60°C (-22°F to 140°F)</p> <p>Operating Relative Humidity: 8% to 80% (non-condensing)</p> <p>Non-operating Relative Humidity: 8% to 90% (non-condensing)</p>
Motherboard	<a href="#">Super X14DBT-B</a>
Chassis	CSE-827BD2-R2K22P